

COMPARISON OF ADJUSTABLE PEDESTALS SERIES

	SERIES SUPPORT PADS FOR TILES	SERIES SPIRAL FOR TILES & JOISTS	SERIES RAPTOR FOR JOISTS	SERIES STANDARD FOR TILES & JOISTS	SERIES MAX FOR TILES & JOISTS	SERIES ALU FOR TILES
Basic features	Fixed height tile spacer support pads.	Adjustable height pedestals for tiles and decking with height increment ~1 mm.	Decking pedestals for wood, WPC and aluminium joists with height increment ~1 mm.	Universal adjustable pedestals for tiles and decking with optimum size and height range.	Large and highest durability adjustable height pedestals for professionals. Terrace with high load and height demands.	Can be used on commercial projects that need to meet a fire classification of construction products & building elements. Steel / Aluminium material with a high weight resistance.
Example of use						
Look ¹						
Height regulation	constant height (stacking, possibility of leveling with rubber shim 1,5 mm)	adjustable height (height increment ~ 1 mm)	adjustable height (height increment ~ 1 mm)	adjustable height (smooth)	adjustable height (smooth)	adjustable height (smooth)
Height range of series	constant height 2, 8*, 10*, 15* or 16* mm (* possible to stack up to 3 pcs.)	adjustable from 10 to 210 mm	adjustable from 15 to 245 mm	adjustable from 30 to 420 mm	adjustable from 45 to 950 mm	adjustable from 40 to 200 mm
Dimension of head / base of the pedestals	<ul style="list-style-type: none"> base 002 - 100 × 100 mm base 008 - 109 × 109 mm base 010, 015 - 146 × 146 mm base 016 - 174,5 × 174,5 mm 	<ul style="list-style-type: none"> head - 168 × 168 mm base - 168 × 168 mm 	<ul style="list-style-type: none"> wedge S - 60 × 120 mm base S - 60 × 120 mm wedge M, L, XL - 60 × 78 mm base L - 120 × 120 mm 	<ul style="list-style-type: none"> head - 100 × 100 mm base - 177 × 177 mm 	<ul style="list-style-type: none"> head - 145 × 145 mm base - 210 × 210 mm 	<ul style="list-style-type: none"> head - 120 × 120 mm base - 130 × 130 mm
Load ²	to 2500 kg	to 2400 kg	to 1000 kg	to 1100 kg	to 1700 kg	to 2000 kg
Leveling an inclined substrate ³	rubber pad	from 0 to 6% self-regulation (self leveling head)	from 0 to 7% manual regulation (slope corrector)	from 0 to 7% self-regulation (self leveling head)	from 0 to 14% self-regulation to 6% (self leveling head) manual regulation to 8% (slope corrector)	from 0 to 6% self-regulation
The width of the gap between the tiles	<ul style="list-style-type: none"> built-in gap spacers 3 mm possibility of a 5 mm gap with the use of attached gap spacers 	<ul style="list-style-type: none"> spacer disc 3 or 5 mm gap spacer 3 or 5 mm 	×	<ul style="list-style-type: none"> cross spacer 3 or 5 mm spacer disc 3 or 5 mm 	<ul style="list-style-type: none"> spacer disc 3 or 5 mm gap spacer 3 or 5 mm 	<ul style="list-style-type: none"> built-in gap spacers 3 mm
Installation of joists	×	<ul style="list-style-type: none"> separate adapter for joist 	<ul style="list-style-type: none"> built-in joist adapter 	<ul style="list-style-type: none"> separate adapter for joist 	<ul style="list-style-type: none"> separate adapter for joist 	×
Support heights	<ul style="list-style-type: none"> 2 mm DDP 002 8 mm DDP 008 10 mm DDP 010 15 mm DDP 015 16 mm DDP 016 	<ul style="list-style-type: none"> from 10 to 17 mm SPIRAL 010-017 from 17 to 30 mm SPIRAL 017-030 from 30 to 50 mm SPIRAL 030-050 from 50 to 70 mm SPIRAL 050-070 from 70 to 90 mm SPIRAL 070-090 from 90 to 110 mm SPIRAL 090-110 from 110 to 130 mm SPIRAL 110-130 from 130 to 150 mm SPIRAL 130-150 from 150 to 170 mm SPIRAL 150-170 from 170 to 190 mm SPIRAL 170-190 from 190 to 210 mm SPIRAL 190-210 	<ul style="list-style-type: none"> from 15 to 35 mm RAPTOR S from 35 to 65 mm RAPTOR M from 65 to 95 mm RAPTOR L from 95 to 125 mm RAPTOR XL from 125 to 155 mm RAPTOR XL1 from 155 to 185 mm RAPTOR XL2 from 185 to 215 mm RAPTOR XL3 from 215 to 245 mm RAPTOR XL4 	<ul style="list-style-type: none"> from 30 to 45 mm DDP 030-045 from 45 to 70 mm DDP 045-070 from 70 to 120 mm DDP 070-120 from 120 to 220 mm DDP 120-220 from 220 to 320 mm DDP 220-320 from 320 to 420 mm DDP 320-420 	<ul style="list-style-type: none"> from 45 to 75 mm MAX 045-075 from 75 to 150 mm MAX 075-150 from 150 to 350 mm MAX 150-350 from 350 to 550 mm MAX 350-550 from 550 to 750 mm MAX 550-750 from 750 to 950 mm MAX 750-950 	<ul style="list-style-type: none"> from 40 to 50 mm ALU 040-050 from 50 to 60 mm ALU 050-060 from 60 to 75 mm ALU 060-075 from 70 to 95 mm ALU 070-095 from 90 to 115 mm ALU 090-115 from 110 to 135 mm ALU 110-135 from 130 to 155 mm ALU 130-155 from 150 to 175 mm ALU 150-175 from 170 to 200 mm ALU 170-200
Additional accessories	<ul style="list-style-type: none"> Gap spacer 5 mm L5 Rubber shim 1,5 mm SH100 (DDP 008) Rubber shim 1,5 mm SH145 (DDP 010, DDP 015) Rubber shim 1,5 mm SH175 (DDP 016) SBR rubber pad SBR 100/3 3 mm (DDP 002, DDP 008) SBR rubber pad SBR 100/8 8 mm (DDP 002, DDP 008) SBR rubber pad SBR 200/3 3 mm (DDP 010, DDP 015, DDP 016) SBR rubber pad SBR 200/8 8 mm (DDP 010, DDP 015, DDP 016) 	<ul style="list-style-type: none"> Joist adapter AD ⁴ Spacer disc 3 mm D3 ⁴ Spacer disc 5 mm D5 ⁴ Gap spacer 3 mm L3 Gap spacer 5 mm L5 Rubber shim SH145 1,5 mm Self leveling head 0-6% LE MAX 20 mm Up to wall clip DDPWAP 2,5 mm Side finishing closure plate DDP CP 3,5 mm Height coupler DS 60 60 mm SBR rubber pad SBR 200/3 3 mm SBR rubber pad SBR 200/8 8 mm 	<ul style="list-style-type: none"> Wedge raiser P30 30 mm Slope corrector 0-7% KN 10 mm Protection pad PO 2 mm Sound reduction pad PA 10 mm SBR rubber pad SBR 170/3 3 mm 	<ul style="list-style-type: none"> Drill driver bit tool PPK Joist adapter AD ⁴ Cross spacer 3 mm K3 ⁴ Cross spacer 5 mm K5 ⁴ Spacer disc 3 mm L3 Spacer disc 5 mm L5 Rubber shim SH100 1,5 mm Self leveling head 0-7% LE 16 mm Up to wall clip DDPWAP 2,5 mm Side finishing closure plate DDP CP 3,5 mm Height coupler DS 100 100 mm SBR rubber pad SBR 200/3 3 mm SBR rubber pad SBR 200/8 8 mm 	<ul style="list-style-type: none"> Drill driver bit tool PPK Key from the top MPK Windproof system WP Joist adapter AD ⁴ Spacer disc 3 mm D3 ⁴ Spacer disc 5 mm D5 ⁴ Gap spacer 3 mm L3 Gap spacer 5 mm L5 Rubber shim SH145 1,5 mm Self leveling head 0-6% LE MAX 20 mm Up to wall clip DDPWAP 2,5 mm Side finishing closure plate DDP CP 3,5 mm Height coupler DS 200 200 mm Slope corrector 0-8% SC 30,5 mm SBR rubber pad SBR 220/3 3 mm 	×

• ¹ Similar look showing the characteristic structure of the adjustable pedestal. The appearance of the adjustable pedestal, especially the support pads, varies according to their height. • ² Detailed values for individual heights are given in the technical specification.

• ³ Requires additional accessories. • ⁴ Depending on the type of order, it is part of the set.