

ADJUSTABLE PEDESTALS









STANDARD SERIES

- Load resistance up to 1100 kg on each center loaded pedestal.
- Only 4 pedestals heights to reach basic height adjustment between 30 - 220 mm.
- Reach height 420 mm with 2 height couplers only.
- Select 3 mm or 5 mm tab size for pavers.
- Select joist adapter for decking.
- Fast installation with unique driller bit tool.
- Manual adjustment for precise height regulation.
- Self leveling head automatically adjust to slope (0-7%).
- Additional accessories as: Rubber shim, Up to wall perimeter clip, Vertical closure clip, Rubber SBR pads, Driller bit tool.
- Made in EU.



Copyright 2022 DD GROUP. All rights reserved.

STANDARD SERIES

	Model No.	Description	Range	Notes
	 STANDARD 030-045	Adjustable Pedestal	30 - 45 mm	Smooth height adjustment.
	 STANDARD 045-070	Adjustable Pedestal	45 - 70 mm	Smooth height adjustment.
Pedestals	 STANDARD 070-120	Adjustable Pedestal	70 - 120 mm	Smooth height adjustment.
	 STANDARD 120-220	Adjustable Pedestal	120 - 220 mm	Smooth height adjustment.
	 DS100	Height coupler	100 mm	Insert DS100 into STANDARD 120-220 base or another DS100 to reach up to 420 mm.
	 K3 K5	Cross spacer	-	Select 3 mm or 5 mm paver gap spacer.
Tabs	 L3 L5	Gap spacer	-	Select 3 mm or 5 mm paver gap spacer.
	 AD	Joist adapter	-	For decking joist fixing with pedestals.

Accessories		SH100	Rubber shim	Adds 1,5 mm in height	Noise cancellation and tile thickness compensation.
		LE	Self leveling head LE 0-7%	Adds 16 mm in height	Self leveling of the terrace with a slope range from 0% to 7%.
		DDPWAP	Up to wall clip	Adds 2,5 mm in height	Use to create a gap between perimeter tile and wall. Prevent tiles displacement and makes a spare space for tiles thermal expansion.
		DDP CP	Side finishing closure plate	Adds 3,5 mm in height	It is used to make vertical masking of the ventilated terrace. Two pieces increase the height of the bracket by 7 mm.
		PPK	Drill driver bit tool	-	Helps with fast height adjustment of the pedestals.
		SBR 200/3 SBR 200/8	SBR rubber pad	Adds 3 or 8 mm in height	Select 3 mm or 8 mm height option. Placed under the pedestal gives additional protection of the water membrane. Also gives additional noise cancellation.
		SBR 200/3 SBR 200/8	SBR rubber pad	Adds 3 or 8 mm in height	

Copyright 2022 DD GROUP. All rights reserved.



IMPORTANT: Refer to DD PEDESTALS product specifications to ensure proper use and installation. Find specifications at www.ddgro.eu