



ADJUSTABLE PEDESTALS

STANDARD SERIES

- Load resistance up to 1100 kg on each center loaded pedestal.
- Only 4 pedestals heights to reach basic height adjustment between 30 - 220 mm (1 3/16" - 8 5/8").
- Reach height 420 mm (16 1/2") with 2 height couplers only.
- Select 3 mm or 5 mm (1/8" or 3/16") tab size for pavers.
- Select joist adapter for decking.
- Fast installation with unique driller bit tool.
- Manual adjustment for precise height regulation.
- Self leveling head automatically adjust to slope (0-7%).
- Additional accessories as: Rubber shim, Up to wall perimeter clip, Vertical closure clip, Rubber SBR pads, Driller bit tool.
- Made in EU.



Copyright 2022 DD GROUP. All rights reserved.

STANDARD SERIES

	Model No.	Description	Range	Notes
	 STANDARD 030-045	Adjustable Pedestal	30 - 45 mm (1 3/16" - 1 12/16")	Smooth height adjustment.
	 STANDARD 045-070	Adjustable Pedestal	45 - 70 mm (1 12/16" - 2 3/4")	Smooth height adjustment.
Pedestals	 STANDARD 070-120	Adjustable Pedestal	70 - 120 mm (2 3/4" - 4 3/4")	Smooth height adjustment.
	 STANDARD 120-220	Adjustable Pedestal	120 - 220 mm (4 3/4" - 8 5/8")	Smooth height adjustment.
	 DS100	Height coupler	100 mm (4")	Insert DS100 into STANDARD 120-220 base or another DS100 to reach up to 420 mm (16 1/2").
	 K3 K5	Cross spacer	-	Select 3 mm (1/8") or 5 mm (3/16") paver gap spacer.
Tabs	 L3 L5	Gap spacer	-	Select 3 mm (1/8") or 5 mm (3/16") paver gap spacer.
	 AD	Joist adapter	-	For decking joist fixing with pedestals.

Accessories		SH100	Rubber shim	Adds 1,5 mm (1/16") in height	Noise cancellation and tile thickness compensation.
		LE	Self leveling head LE 0-7%	Adds 16 mm (5/8") in height	Self leveling of the terrace with a slope range from 0% to 7%.
		DDPWAP	Up to wall clip	Adds 2,5 mm (1/11") in height	Use to create a gap between perimeter tile and wall. Prevent tiles displacement and makes a spare space for tiles thermal expansion.
		DDP CP	Side finishing closure plate	Adds 3,5 mm (1/8") in height	It is used to make vertical masking of the ventilated terrace. Two pieces increase the height of the bracket by 7 mm (3/11").
		PPK	Drill driver bit tool	-	Helps with fast height adjustment of the pedestals.
		SBR 200/3 SBR 200/8	SBR rubber pad	Adds 3 or 8 mm (1/8" or 5/16") in height	Select 3 mm (1/8") or 8 mm (5/16") height option. Placed under the pedestal gives additional protection of the water membrane. Also gives additional noise cancellation.
		SBR 200/3 SBR 200/8	SBR rubber pad	Adds 3 or 8 mm (1/8" or 5/16") in height	

Copyright 2022 DD GROUP. All rights reserved.



IMPORTANT: Refer to DD PEDESTALS product specifications to ensure proper use and installation. Find specifications at www.ddgro.eu